

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>AUG 1999</b>		2. REPORT TYPE		3. DATES COVERED <b>00-00-1999 to 00-00-1999</b>	
4. TITLE AND SUBTITLE <b>Strategies for Modeling the Interaction of Devices, Circuits and Fields</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>North Carolina State University, Department of Electrical and Computer Engineering, Raleigh, NC, 27695</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>Proceedings of 1999 URSI General Assembly, 13-21 Aug 1999, Toronto</b>					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>1</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

# Strategies for Modeling the Interaction of Devices, Circuits and Fields

Michael B. Steer, The University of Leeds, James W. Mink, North Carolina State University, and, James F. Harvey, U.S. Army Research Office  
Institute of Microwaves and Photonics, School of Electronic and Electrical Engineering, The University of Leeds, Leeds, LS2 9JT, United Kingdom. e-mail: m.b.steer@ee.leeds.ac.uk

Many of the microwave engineering developments have come about when the electromagnetic environment has been transformed into a circuit abstraction. Three particular developments exemplify this modeling procedure. The first of these is the modeling work undertaken for radar development during the Second World War: Marcuvitz's book [1] showed how discontinuities in waveguide could be modeled by lumped element equivalents. The second work, Collin's *Foundations of Microwave Engineering* book, presented a formalism for treating distributed structures as circuit elements [2]. A third example is the pioneering work of Eisenhart and Khan [3] which presented an approach to modeling waveguide-based structures as circuit elements. In this work it was shown that quite sophisticated and accurate models could be developed for three-dimensional waveguide systems.

One fundamental issue that arises in modeling electrically large systems as a circuit representation is the assignment of system ground. Currently circuit simulators use a nodal approach in which voltages are assigned to nodes and each of these voltages is referred to a common reference point commonly called ground. In a spatially distributed system, a common reference point cannot always be defined as the spatial separation of a node and its reference point cannot be tolerated. Microstrip networks are examples of distributed structures for which reasonable approximations have been made so that they can be treated as elements in conventional circuit simulators. So, the accepted view is that the ground plane can be treated as a global reference point (common ground) even though this implies, and requires, that charges can instantaneously redistribute on the ground plane.

In this talk the global modeling of distributed microwave circuits — such as a spatial power combiner — integrating electromagnetic, circuit and thermal modeling is discussed. The talk discusses the developments in circuit theory necessary to model distributed microwave circuits and thermal networks. Then a strategy for integrating electromagnetic models into steady-state (harmonic balance) and transient circuit analysis will be presented. Then integration of thermal analysis is described. Measured and simulated results for a grid amplifier are used to illustrate the discussion.

This work was supported by a MURI program sponsored by the U.S. Army Research Office through a contract with Clemson University.

- [1] N. Marcuvitz, *Waveguide Handbook*. New York: McGraw Hill, Massachusetts Institute of Technology, Radiation Laboratory series, No. 10, 1951.
- [2] R. E. Collin, *Foundations for Microwave Engineering*, Tokyo: McGraw-Hill, 1966
- [3] R. L. Eisenhart and P. J. Khan, "Theoretical and experimental analysis of a waveguide mounting structure," *IEEE Trans. Microwave Theory Tech.*, Vol. 19, Aug. 1971, pp. 706-719.